


3HS SERIES, THREE ELEMENT STAINLESS STEEL HEATERS					
WATTS	VOLTS	HOT ZONE In./(mm)	OVERALL LENGTH In./(mm)	MODEL NUMBER	SHIP WGT. Lbs./(kg)
3000	240	10	17	3HS3217-**-**	9
	480	(255)	(430)	3HS3417-**-**	(4)
4500	240	16	23	3HS4.5223-**-**	10
	480	(405)	(585)	3HS4.5423-**-**	(4.5)
7500	240	20	29	3HS7.5229-**-**	12
	480	(510)	(735)	3HS7.5429-**-**	(5.5)
10500	240	25	34	3HS10.5234-**-**	14
	480	(635)	(865)	3HS10.5434-**-**	(6.5)

Three phase standard, single phase available as option. Add "-1" before thermal protector designator.

## Product Features and Benefits:

- ◆ **SUPERIOR CHEMICAL RESISTANCE:** For use in most aqueous alkaline solutions and rinse tanks. Check solution recommendation chart or with your chemical supplier for proper sheath material selection.
- ◆ **RUGGED CONSTRUCTION:** Heavy wall metal sheaths in 316 stainless steel.
- ◆ **OUTSTANDING PERFORMANCE:** Watt densities of 40 watts per square inch (6.2 w/cm<sup>2</sup>) use minimal space and ensure long service life.
- ◆ **CORROSION RESISTANT HEAD:** Vapor tight, flame retardant polypropylene terminal enclosure with 3-foot (.9m) flexible PVC liquid tight conduit.
- ◆ **SAFETY FEATURES:**
  - Grounded construction.
  - Thermal protector built in. Replaceable PI fuse standard for solutions up to 180°F (82°C).
  - Non-floating construction.
- ◆ **CERTIFICATIONS:** UL, CSA and CE.
- ◆ **SIZES:** 3,000 watts to 10,500 watts.
- ◆ **VOLTAGES:** 240 or 480 volts. 208, 380, 415, 600 and other voltages available. Three phase standard, single phase available.
- ◆ **OPTIONS AVAILABLE** (consult factory):
  - Replaceable thermal protectors:
    - PIM: for solutions from 180°F (82°C) to 230°F (110°C).
    - PIH: for solutions from 230°F (110°C) to 300°F (150°C).
  - Resettable thermal protectors:
    - PII: for solutions up to 180°F (82°C).
    - PIIM: for solutions from 180°F (82°C) to 230°F (110°C).
    - PIIH: for solutions from 230°F (110°C) to 300°F (150°C).
  - Special configurations and lengths.
  - Longer wire and conduit lengths.
  - Lower watt densities for highly viscous solutions.
  - Titanium elements.
  - Temperature and level controls sized to match the heater.

## DIMENSIONS



### 3 ELEMENT OVER THE SIDE HEATER

Series	Wattage	Voltage	Overall Length	Options	Type of Fuse	Wire and Conduit Length
	3 = 3000 4.5 = 4500 7.5 = 7500 10.5 = 10500	2 = 240 4 = 480 -208- = 208 -380- = 380 -415- = 415 -600- = 600	17 = 3kW 23 = 4.5kW 29 = 7.5kW 34 = 10.5kW			36" length standard (no designator) specify variations from standard Ex: -X84 = 84"
	3HS = 3 element, 316 stainless steel					
X = any special configuration not called out in the part number (specify in clear text) no designator = three phase power (standard) -1 = single phase power						
					<b>Replaceable Fuse</b>	
					-PI (std)	for solutions up to 180°F
					-PIM	for 180° - 230°F solutions
					-PIH	for 230° - 300°F solutions
					<b>Resettable Fuse</b>	
					(additional control components required)	
					-PII	for solutions up to 180°F
					-PIIM	for 180° - 230°F solutions
					-PIIH	for 230° - 300°F solutions

### ORDERING EXAMPLE:

3HS3417-PII

3 element, 316 stainless steel, 3000 watt, 480 volt, 17" overall length, PII fuse.

